

TOLERANCE ON OUTSIDE DIAMETER WALL THICKNESS, WEIGHT AND LENGTH OF PIPE

SPEC.	TYPE	OUTSIDE DIAMETER		WALL THICKNESS	WEIGHT	LENGTH							
		PIPE BODY	PIPE ENDS (PLAIN END)			NOMINAL		AVG(min)		MINIMUM		MAXIMUM	
						ft.	Mtr	ft.	Mtr	ft.	Mtr	ft.	Mtr
API 5CT	E,S	< 4.1/2" (114.3 mm) ± 0.031" (0.79 mm)	N / A	+ Not Limited	Single Length = + 6.5%, - 3.50%			Range- 1		Range-2		Range - 3	
		≥ 4. 1/2" (114.3 mm) + 1%, - 0.5%		-12.5%	Carloads ≥ 40,000 lbs (18,144 kg) : - 1.75%	CASING	16-25		25-34		34-48	(feet)	
					Carloads < 40,000 lbs (18,144 kg) : - 3.50%	TUBING	20-24		28-32		38-42	(feet)	
							(6.10-7.32)		(8.54-9.75)		(11.58-12.80)	(mtr)	
						Pup Joints 2,3,4,6,8,10 & 12 Ft. Tolereance = ± 3"							

E = ERW S = Seamless